

STANDARD
CONSTRUCTION
DETAILS

WASTEWATER

AUGUST 2010


Addison![®]

PUBLIC WORKS DEPARTMENT


TABLE OF CONTENTS

WASTEWATER

P.V.C. WASTEWATER MAIN EMBEDMENT	SD-WW01
TWO-WAY CLEANOUT - NEW CONSTRUCTION	SD-WW02
CAST IRON CLEANOUT FRAME & COVER	SD-WW03
CAST-IN-PLACE MANHOLE	SD-WW04
SEALED TYPE 'S' CAST-IN-PLACE MANHOLE	SD-WW05
PRECAST CONCRETE PIPE MANHOLE, ALTERNATE "A"	SD-WW06
PRECAST CONCRETE PIPE MANHOLE, ALTERNATE "B"	SD-WW07
EXTERNAL DROP MANHOLE CONNECTION	SD-WW08
INTERIOR DROP MANHOLE CONNECTION	SD-WW09
VENTED MANHOLE	SD-WW10
CAST IRON MANHOLE FRAME AND COVER	SD-WW11
PRESSURE TYPE MANHOLE FRAME AND COVER	SD-WW12
WASTEWATER MANHOLE LINE INTERSECTION & 'C-T' PIPE ADAPTER	SD-WW13
WASTEWATER MANHOLE FALSE BOTTOM	SD-WW14
ABANDONMENT OF MANHOLE	SD-WW15
CASING	SD-WW16



TYPICAL P.V.C. WASTEWATER MAIN EMBEDMENT



NOTE:

1. CEMENT STABILIZED SAND SHALL HAVE A MINIMUM OF 10% CEMENT PER CUBIC YARD OF CEMENT STABILIZED SAND MIXTURE, BASED ON LOOSE DRY WEIGHT VOLUME (AT LEAST 2.5 BAGS OF CEMENT PER CUBIC YARD OF MIXTURE). THE USE OF BROWN COLORING IN CEMENT STABILIZED SAND IS REQUIRED FOR PRESSURE RATED WASTEWATER MAIN AND LATERAL BEDDING.

P.V.C. WASTEWATER MAIN CEMENT STABILIZED SAND EMBEDMENT



PUBLIC WORKS DEPARTMENT



P.V.C. WASTEWATER MAIN EMBEDMENT

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010


REV DATE:
-

SHEET :
SD-WW01



NOTES:

1. WASTEWATER LATERALS ARE TO BE CONSTRUCTED TO CLEAR EXISTING AND PROPOSED FACILITIES, SUCH AS STORM DRAIN MAINS, RETAINING WALLS, OTHER UTILITIES, ETC.
2. THE WASTEWATER LATERAL SHALL HAVE MINIMUM COVER OF 4'-0" BELOW THE PROPOSED CURB GRADE AT THE PROPERTY LINE, DETERMINED FROM PAVING GRADE, OR AS REQUIRED TO MAINTAIN A MINIMUM OF 2.0% GRADE, OR AS DIRECTED BY THE OWNER.



Addison!

PUBLIC WORKS DEPARTMENT


TWO-WAY CLEANOUT
NEW CONSTRUCTION

STANDARD CONSTRUCTION DETAILS
WASTEWATER


DATE:
AUGUST, 2010

REV DATE:
-


SHEET :
SD-WW02




COVER
N.T.S.





CLEANOUT FRAME TOP
N.T.S.




SECTION "A-A"
N.T.S.



SECTION "B-B"
N.T.S.



CLEANOUT FRAME BOTTOM
N.T.S.



ASSEMBLY VIEW
N.T.S.

1. THE WORDS "WASTEWATER LATERAL CLEANOUT" SHALL BE CAST INTO TOP OF COVER.
2. MATERIALS TO BE CAST IRON.

Addison!

PUBLIC WORKS DEPARTMENT

CAST IRON
CLEANOUT FRAME & COVER


STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010


REV DATE:
-

SHEET :
SD-WW03

PRESSURE TYPE MANHOLE
FRAME AND COVER, MANHOLE
FRAME CAST IN ROOF
W/CONTINUOUS POUR FROM
BASE.




PRESSURE TYPE MANHOLE
FRAME AND COVER, MANHOLE
FRAME CAST IN ROOF
W/CONTINUOUS POUR FROM
BASE.



TRANSITION DETAIL FOR 5' AND 6'


PRESSURE TYPE MANHOLE
FRAME AND COVER

CONSTRUCTION JOINT
WITH KEYWAY WATERSTOP
AND #3'S 12" O.C. EXTENDING
9" INTO WALL (NOT REQUIRED
FOR CONTINUOUS POUR).



SECTION A-A

#3'S AT
6" O.C.E.W.



MANHOLE LID SHOULD
BE IN LINE WITH
UPSTREAM PIPE
WHERE POSSIBLE

ROOF OPTIONS

NOTES:

- IF FALSE MANHOLE BOTTOMS ARE REQUIRED, THEY SHALL BE CONSTRUCTED, INSTALLED, AND REMOVED PER WASTEWATER MANHOLE FALSE BOTTOM STD. DETAIL.
- WHERE MANHOLE'S ARE OUTSIDE OF PAVEMENT, FRAME & COVER SHALL BE CENTERED IN 5'x5' CONCRETE PAD CLASS 'A' CONCRETE, 4" THICK
- ALL MANHOLES SHALL PASS VACUUM TEST PER NCTCOG SPECIFICATIONS
- LID SHALL BE GASKETED, BOLT-DOWN TYPE WITH STAINLESS STEEL BOLTS.
- SEALED MANHOLE SHALL BE EPOXY COATED TO PREVENT INTERNAL CORROSION. EPOXY COATING SHALL BE RAVEN 405, OR APPROVED EQUAL AND SHALL BE A MINIMUM 200 MILS THICKNESS AND SHALL BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.

Addison!

PUBLIC WORKS DEPARTMENT


SEALED TYPE 'S'
CAST-IN-PLACE
MANHOLE

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-

SHEET :
SD-WW05



NOTES:

1. IF FALSE MANHOLE BOTTOMS ARE REQUIRED, THEY SHALL BE CONSTRUCTED, INSTALLED, AND REMOVED PER WASTEWATER MANHOLE FALSE BOTTOM STD. DETAIL.
2. WHERE MANHOLE'S ARE OUTSIDE OF PAVEMENT, FRAME & COVER SHALL BE CENTERED IN 5'x5' CONCRETE PAD CLASS 'A' CONCRETE, 4" THICK
3. ALL MANHOLES SHALL PASS VACUUM TEST AS PER NCTCOG SPECIFICATIONS

Addison!

PUBLIC WORKS DEPARTMENT

PRECAST CONCRETE
PIPE MANHOLE
ALTERNATE "A"

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-

SHEET :
SD-WW06

MANHOLE RIM TO BE SET FLUSH WITH PAVEMENT OR 1" TO 4" ABOVE GRADE IN NON-PAVED AREAS

SEE CAST IRON MANHOLE FRAME & COVER DETAIL

EXIST. GRADE

EXIST. PVMT.

1/2" NON SHRINK GROUT COATING

30"

NEOPRENE "O-RING" GASKET AND MASTIC.

3' TO 5'
3' FOR 4' MANHOLE

4', 5' OR 6'

VARIES

INTERMEDIATE RISER
(USE MINIMUM NO. OF RISERS)

REFER TO NCTCOG SPECIFICATION (LATEST EDITION) FOR :

1. CONCRETE CLASS.
2. CONCRETE PIPE MATERIAL.
3. MANHOLE MATERIAL.
4. RUBBER GASKET JOINT.

COUPLING WITH O-RING RUBBER GASKET KOR-N-SEAL, OR APPROVED EQUAL

TOP OF PIPE

BASE RISER
(VARIES)

EMBEDMENT AS SPECIFIED BY STANDARD DETAILS.

12"

5"

12" MIN.

ROCK FOUNDATION

GEOTEXTILE MATERIAL

NOTES:

1. IF FALSE MANHOLE BOTTOMS ARE REQUIRED, THEY SHALL BE CONSTRUCTED, INSTALLED, AND REMOVED PER WASTEWATER MANHOLE FALSE BOTTOM STD. DETAIL.
2. WHERE MANHOLE'S ARE OUTSIDE OF PAVEMENT, FRAME & COVER SHALL BE CENTERED IN 5'x5' CONCRETE PAD CLASS 'A' CONCRETE, 4" THICK
3. ALL MANHOLES SHALL PASS VACUUM TEST AS PER NCTCOG SPECIFICATIONS

Addison!

PUBLIC WORKS DEPARTMENT


PRECAST CONCRETE
PIPE MANHOLE
ALTERNATE "B"

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-

SHEET :
SD-WW07



EXTERNAL DROP MANHOLE CONNECTION

Addison!

PUBLIC WORKS DEPARTMENT


EXTERNAL DROP MANHOLE CONNECTION

STANDARD CONSTRUCTION DETAILS WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-

SHEET :
SD-WW08



INTERIOR DROP MANHOLE CONNECTION

Addison!

PUBLIC WORKS DEPARTMENT


INTERIOR DROP MANHOLE
CONNECTION

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-

SHEET :
SD-WW09



Addison!

PUBLIC WORKS DEPARTMENT


VENTED MANHOLE

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-




SHEET :
SD-WW10



NOTES:

1. THERE SHALL BE SMOOTH TRANSITION BETWEEN THE FRAME GRADE RING, OR THE GRADE RING AND THE CONE.
2. CONCRETE EXTENSION RINGS MAY BE PRECAST OR CAST-IN-PLACE. BRICK EXTENSION RINGS WILL NOT BE ALLOWED.
3. STANDARD EXTENSIONS SHALL BE 2", 3", 4", 6", AND 12". EXTENSIONS SHALL BE SIZED TO MINIMIZE THE NUMBER REQUIRED TO RAISE THE MANHOLE. NO MORE THAN A TOTAL OF 14" OF EXTENSION WILL BE ALLOWED ON ANY MANHOLE.

RING TO BE ATTACHED TO CONE WITH THREE 3/4" DIA. STAINLESS STEEL ALL THREAD BOLTS. BOLTS TO BE SECURED IN PLACE WITH EPOXY CONCRETE.



✓ DESIGNATES MACHINE SURFACE



PUBLIC WORKS DEPARTMENT




CAST IRON MANHOLE FRAME AND COVER

STANDARD CONSTRUCTION DETAILS WASTEWATER

DATE: AUGUST, 2010

REV DATE: -

SHEET : SD-WW11



√ DESIGNATES MACHINE SURFACE

Addison!

PUBLIC WORKS DEPARTMENT


PRESSURE TYPE MANHOLE
FRAME AND COVER

STANDARD CONSTRUCTION DETAILS
WASTEWATER

DATE:
AUGUST, 2010


REV DATE:
-

SHEET :
SD-WW12




T = WALL THICKNESS
 D = MANHOLE DIAMETER
 d = PIPE DIAMETER

PLAN
 N.T.S.



SECTION A-A
 N.T.S.

WASTEWATER MANHOLE LINE INTERSECTION



'C-T' PIPE ADAPTER



PUBLIC WORKS DEPARTMENT

WASTEWATER MANHOLE LINE INTERSECTION & 'C-T' PIPE ADAPTER

STANDARD CONSTRUCTION DETAILS WASTEWATER


DATE: AUGUST, 2010	REV DATE: -	SHEET : SD-WW13
-----------------------	----------------	--------------------

INSTALLATION

FALSE MANHOLE BOTTOM SHALL BE FURNISHED AND INSTALLED IN ALL MANHOLES CONSTRUCTED IN ADVANCE OF PAVING. THESE FALSE MANHOLE BOTTOMS WILL BE INSTALLED AT A TIME DIRECTED BY THE ENGINEER BUT WILL USUALLY BE AFTER ALL WORK IS COMPLETED ON THE WASTEWATER SYSTEM INCLUDING THE AIR TEST, BUT PRIOR TO THE FINAL INSPECTION.


REMOVAL

FALSE MANHOLE BOTTOM SHALL BE REMOVED AFTER THE FINAL APPURTENANCES ADJUSTMENT INSPECTION. THE PAVING CONTRACTOR AND OWNER'S REPRESENTATIVE WILL COORDINATE THE REMOVAL OF THE FALSE BOTTOMS.



METAL STRAP HINGES (MIN. 3" LONG) W/BOLTS

INSTALLATION AND REMOVAL POSITION



PLAN VIEW



PUBLIC WORKS DEPARTMENT

WASTEWATER MANHOLE FALSE BOTTOM


STANDARD CONSTRUCTION DETAILS WASTEWATER

DATE: AUGUST, 2010

REV DATE: -

SHEET : SD-WW14

MH. TO BE REMOVED A MIN.
OF 3'-0" BELOW GRADE.



Addison!

PUBLIC WORKS DEPARTMENT


ABANDONMENT OF MANHOLE

STANDARD CONSTRUCTION DETAILS WASTEWATER

DATE:
AUGUST, 2010

REV DATE:
-

SHEET :
SD-WW15




TYPICAL CASING SECTION


CARRIER PIPE SIZE (IN)	STEEL ENCASEMENT O.D. (IN)	STEEL ENCASEMENT WALL THICKNESS (IN)
6	14	1/4
8	18	1/4
12	21	1/4
18	27	3/8
21	30	3/8
24	36	3/8
27	39	1/2

FOR ALL CARRIER PIPES OVER 27": THE STEEL ENCASEMENT PIPE SHALL BE 12" LARGER THAN THE CARRIER PIPE AND THE STEEL ENCASEMENT WALL THICKNESS SHALL BE 1/2".

OVERCUTTING SHALL BE FILLED WITH HYDRAULICALLY PLACED NON-SHRINK GROUT AS PER ASTM C476



WASTEWATER ENCASEMENT



INSULATOR SPACING DETAIL

NOTES:

1. HIGH DENSITY POLYETHYLENE SPACERS, RACI OR EQUAL, SHALL BE USED. WHERE NO CASING PIPE IS REQUIRED OVERCUTTING AROUND UTILITY SHALL BE FILLED WITH HYDRAULICALLY PLACED NON-SHRINK GROUT AS PER ASTM C476.
2. ENCASEMENT PIPE SHALL BE HIGH DENSITY STEEL PIPE. ALL JOINTS TO BE WELDED 100%.



PUBLIC WORKS DEPARTMENT

CASING

STANDARD CONSTRUCTION DETAILS WASTEWATER

DATE: AUGUST, 2010

REV DATE: -

SHEET : SD-WW16